Flat hose

Premium heavy duty PVC Water discharge hose

With higher performance in abrasion, pressure and durability.

Applications:

Agriculture
Construction
Industrial project
Mining and dewatering

Technical Characteristics	
Tube and Cover	Durable PVC material with a good abrasion, chemical and UV resistance
Reinforcement	*Hi performance reinforcement designed for higher pressure.*
Color	Red brick
Working Pressure	Varies by sizes
Nominal Burst Pressure	*Safety factor 3:1*
Temperature	-5 °F - +170 °F / -20 °C + 76 °C

Part no.	Inner Diameter		Wall Thickness		W. P at 68 °F	Length	Weight
	INCH	MM	INCH	MM	PSI	Ft / mtr	Lb/ft
BRFW150-150-300	1 1/2”	38	0.087	2.2	150	300/91	0.23
BRFW150-200-300	2”	50.8	0.091	2.3	150	300/91	0.32
BRFW150-250-300	2 1/2“	63.5	0.095	2.4	150	300/91	0.41
BRFW150-300-300	3”	76.2	0.098	2.5	150	300/91	0.52
BRFW150-400-300	4”	101.6	0.110	2.8	125	300/91	0.76
BRFW150-600-300	6”	152.4	0.118	3.0	115	300/91	1.21
BRFW150-800-100	8”	203.2	0.122	3.1	70	100/30	1.62
BRFW150-1000-100	10”	254.0	0.122	3.1	65	100/30	1.95

Longer length available on request.